

WHAT IS CLAIMED IS

5

1. A liquid crystal display comprising:  
a data driving part taking in image  
display data in response to a clock signal supplied,  
and causing an image display part to display an  
10 image according to the image display data; and  
a control part detecting a change pattern  
of the image display data, and adjusting a phase  
relationship between the clock signal and image  
display data according to the detected change  
15 pattern.

20

2. The liquid crystal display as claimed  
in claim 1, wherein said control part uses the image  
display data for three clock periods of the clock  
signal for detecting the change pattern of the image  
display data.

25

3. The liquid crystal display as claimed  
30 in claim 1, wherein said control part delays only  
the image display data having a logical levels  
changing for each clock period of the clock signal.

35

4. The liquid crystal display as claimed

10015065-12401

in claim 1, wherein said control part delays the clock signal.

5

5. The liquid crystal display as claimed in claim 1, wherein said control part detects the frequency of the clock signal, and adjusts the phase relationship between the clock signal and image data signal according to the detected frequency as well as the detected change pattern.

15

6. A liquid crystal display comprising:  
a data driving part having a plurality of tone-level nodes provided for tone-level voltages generated in accordance with supplied reference voltages, and causing a liquid-crystal display part to display an image according to the tone-level voltages; and

a selecting part selecting from the plurality of tone-level nodes to which the reference voltages are supplied according to a given first control signal.

30

7. The liquid crystal display as claimed in claim 6, wherein said selecting part is built inside of said data driving part, and the reference voltages are provided from the outside of said data driving part.

10015065.121101

8. The liquid crystal display as claimed in claim 6, wherein said data driving part takes in a data signal transferred thereto as the reference voltage, according to a given second control signal,  
5 as the reference voltage.

10 9. A liquid crystal display comprising:  
a plurality of data driving parts causing  
a liquid-crystal display part to display an image  
according to image display data supplied in  
synchronization with a clock signal;  
15 a control part supplying the image data  
signal and clock signal to said plurality of data  
driving parts; and  
a timing correcting part provided in each  
of said plurality of data driving parts, and making  
20 the clock signal and image display data supplied by  
said control part have predetermined phase  
relationship therebetween

25

10. The liquid crystal display as claimed in claim 9, wherein:  
said control part detects signal  
30 transmission time periods required toward the data  
driving parts, generates a correction signal  
according to the detected data transmission time  
periods to be sent to said timing correcting part;  
and  
35 said timing correcting part makes the  
clock signal and image display data have the  
predetermined phase relationship therebetween

10015065 121101

according to the supplied correction signal.

5

11. The liquid crystal display as claimed in claim 9, wherein:

10 said control part supplies a monitoring data signal common for the timing correcting parts; and

each of the timing correcting parts detects a phase difference between the thus-supplied monitoring data signal and the clock signal, and, thereby, make the clock signal and image display data have the predetermined phase relationship therebetween.

20

12. A liquid crystal display comprising:  
a data driving part causing a liquid-crystal display part to display an image according to image display data by a given control signal; and  
25 a control signal generating part built inside of said data driving part, and generating the control signal according to an external signal provided from the outside of said data driving part.

30

13. The liquid crystal display as claimed in claim 12, wherein said external signal comprises  
35 a clock signal for determining timing by which the image data signal is taken in by said data driving part, and an effective display signal for

10045055-33404

determining a scope of the image display data to be used for image display performed by said liquid crystal display part.

5

14. The liquid crystal display as claimed in claim 12, wherein said control signal comprises a latch signal for storing the image display data into a latch circuit from which the image display data is supplied to said liquid-crystal display part.

15

15. The liquid crystal display as claimed in claim 12, wherein said control signal comprises an alternate-current driving signal for performing alternate-current control of a liquid crystal driving voltage to be supplied to the liquid-crystal display part.

25

16. The liquid crystal display as claimed in claim 12, wherein said data driving part uses a voltage obtained through level shift of a voltage provided from the outside of said liquid crystal display for driving the liquid-crystal display part, and causes said liquid-crystal display part to display an image according to the image display data.

35

10045065 121101

17. A liquid crystal display comprising:  
a liquid-crystal display part displaying  
an image; and  
a data driving part taking in image  
5 display data sequentially according to an effective  
display signal used for determining a scope of the  
image display data to be used for image display  
operation performed by said liquid-crystal display  
part, and causing said liquid-crystal display part  
10 to display an image according to the thus-taken-in  
image display data.

10015065 121101